AMENDMENTS TO THE CLAIMS

This listing of claims replaces all prior versions, and listings, of claims in the application:

1   1.   (Cancelled)

1   2.   (Previously Presented) The method of claim 33, wherein displaying the hyperlink
2   is performed in a browser screen.

1   3.   (Previously Presented) The method of claim 33, further comprising associating
2   the hyperlink with a telephone number of a remote party.

1   4.   (Previously Presented) The method of claim 33, further comprising:
2   associating the hyperlink with a logical identifier of a remote party; and
3   accessing rules information to determine further information to add to the logical
4   identifier.

1   5.   (Original) The method of claim 4, further comprising determining if the call is
2   local or long distance and adding prefix information if the call is determined to be long distance.

1   6.   (Previously Presented) A method of making a call, comprising:
2   displaying a hyperlink;
3   receiving an indication of user selection of the hyperlink;
4   generating a call request based on the indication;
5   associating the hyperlink with a logical identifier of a remote party;
6   accessing rules information to determine further information to add to the logical
7   identifier; and
8   providing charge information appended to the logical identifier for a toll call
9   based on accessing the rules information.

1   7.   (Cancelled)

2

1   8.   (Previously Presented) A method of making a call, comprising:

2   displaying a hyperlink;

3   receiving an indication of user selection of the hyperlink; and

4   generating a call request based on the indication,

5   wherein displaying the hyperlink comprises displaying a hyperlink associated

6 with a uniform resource locator,

7   wherein the uniform resource locator contains a telephone number.

1   9.   (Previously Presented) The method of claim 8, wherein displaying the hyperlink

2 comprises displaying a hyperlink associated with a uniform resource locator having a protocol

3 identifier and a string representing a logical identifier of a callee.

1   10.   (Original) The method of claim 9, wherein the logical identifier comprises a

2 telephone number.

1   11.   (Original) The method of claim 9, wherein the protocol identifier comprises a

2 predetermined identifier to identify the uniform resource locator as a telephony-related uniform

3 resource locator.

1   12.   (Previously Presented) The method of claim 33, further comprising copying the

2 hyperlink from a first storage location accessible by a browser to a second storage location

3 accessible by another application routine.

1   13.   (Previously Presented) The method of claim 33, wherein establishing the call

2 session comprises establishing a call session with a remote terminal.

1   14.   (Previously Presented) A device capable of participating in call sessions over a

2   data network, comprising:

3   a display;

4   a hyperlink presentable in the display and selectable by a user; and

5   a controller to generate a call request in response to selection of the hyperlink, the

6   call request comprising a Session Initiation Protocol (SIP) message.

1   15.   (Original) The device of claim 14, further comprising a storage device containing

2   call rules, the controller to access the call rules to determine how the call request is to be

3   generated.

1   16.   (Original) The device of claim 15, the controller to determine if the call request is

2   a local call or a toll call based on the call rules.

1   17.   (Original) The device of claim 15, the controller to add one or more special

2   characters to provide a function based on the call rules.

1   18.   (Previously Presented) A device capable of participating in call sessions over a

2   data network, comprising:

3   a display;

4   a hyperlink presentable in the display and selectable by a user;

5   a controller to generate a call request in response to selection of the hyperlink; and

6   a storage device containing call rules, the controller to access the call rules to

7   determine how the call request is to be generated,

8   the controller to add one or more special characters to provide a function based on

9   the call rules,

10   wherein the function is selected from the group consisting of disabling call

11   waiting, inserting a pause, and navigating an automated attendant.

1   19.   (Previously Presented) A device capable of participating in call sessions over a

2   data network, comprising:

3   a display;

4   a hyperlink presentable in the display and selectable by a user;

5   a controller to generate a call request in response to selection of the hyperlink; and

6   a storage device containing call rules, the controller to access the call rules to

7   determine how the call request is to be generated,

8   the controller to add charge information to a call request based on the call rules.

1   20.   (Original) The device of claim 14, wherein the hyperlink is presentable in a

2   browser screen in the display.

1   21.   (Original) The device of claim 14, wherein the hyperlink is associated with a

2   label that is presentable in the display and a uniform resource locator that is contained in the call

3   request.

1   22.   (Currently Amended) A device capable of participating in call sessions over a

2   data network, comprising:

3   a display;

4   a hyperlink presentable in the display and selectable by a user; and

5   a controller to generate a <u>Session Initiation Protocol (SIP)</u> call request in response

6   to selection of the hyperlink, the <u>SIP</u> call request for establishing a call session over the data

7   network,

8   wherein the hyperlink is associated with a uniform resource locator containing a

9   logical identifier of a callee, the logical identifier being contained in the <u>SIP</u> call request.

1   23.   (Original) The device of claim 22, wherein the uniform resource locator further

2   contains a predetermined protocol identifier to identify the uniform resource locator as a

3   telephony-based uniform resource locator.

1   24.   (Cancelled)

1   25.   (Previously Presented) The article of claim 35, wherein the instructions when

2 executed cause the device to receive the uniform resource locator associated with a

3 predetermined telephony protocol identifier.

1   26.   (Previously Presented) The article of claim 35, wherein the instructions when

2 executed cause the device to present the hyperlink in a browser screen.

1   27.   (Cancelled)

1   28.   (Previously Presented) The article of claim 35, wherein the instructions when

2 executed cause the device to copy the hyperlink from a first storage location accessible by a first

3 application routine to a second storage location accessible by a second application routine.

1   29.   (Currently Amended) A data signal embodied in a carrier wave and containing

2 instructions that when executed cause a terminal to:

3   receive selection of a hyperlink associated with a label that is displayed by the

4 terminal and a uniform resource locator; and

5   generate a <u>Session Initiation Protocol (SIP)</u> call request for establishing a call

6 session over a data network, the <u>SIP</u> call request containing a callee identifier contained in the

7 uniform resource locator.

1   30.   (Currently Amended) A device capable of participating in call sessions over a

2 packet-based data network, comprising:

3   a display;

4   a storage device to store hyperlinks associated with identifiers of callees;

5   a controller; and

6   a routine executable on the controller to present at least one of the hyperlinks on

7 the display and to generate a <u>Session Initiation Protocol (SIP)</u> call request to establish a call

8 session over the packet-based data network in response to selection of the at least one hyperlink.

1   31.   (Original) The device of claim 30, further comprising an telephone directory

2 routine executable on the controller, the telephone directory routine to add the hyperlink to an

3 address directory.

1   32.   (Original) The device of claim 30, further comprising an electronic mail routine

2 executable on the controller, the electronic mail routine to add the hyperlink to a message.

1   33.   (Previously Presented) A method of making a call, comprising:

2   displaying, in a display of a terminal, a hyperlink;

3   receiving, by the terminal, an indication of user selection of the hyperlink;

4   generating, by the terminal, a call request for establishing a call session over a

5 packet-based network based on the indication;

6   sending, by the terminal, the call request over the packet-based network;

7   communicating, by the terminal, voice data over the packet-based network in the

8 call session,

9   wherein communicating the voice data over the packet-based network comprises

10 communicating the voice data over an Internet Protocol network.

1   34.   (Cancelled)

1   35.   (Previously Presented) An article comprising one or more storage media

2   containing instructions that when executed cause a device to:

3   present a hyperlink in a display of the device;

4   receive an indication of selection of the hyperlink;

5   receive a uniform resource locator associated with the hyperlink; and

6   generate a call request containing information in the uniform resource locator, the

7   call request to establish a call session over a packet-based network,

8   wherein generating the call request comprises generating a Session Initiation

9   Protocol message.

1   36.   (Cancelled)

1   37.   (Previously Presented) The device of claim 30, wherein the routine comprises a

2   Session Initiation Protocol stack.

1   38.   (Previously Presented) The device of claim 30, further comprising an Internet

2   Protocol layer to communicate data in the call session.

1   39.   (Previously Presented) The method of claim 33, wherein sending the call request

2   comprises sending, by the terminal, a Session Initiation Protocol call request over the packet-

3   based network.

1   40.   (Previously Presented) The method of claim 8, wherein generating the call

2   request comprises generating a Session Initiation Protocol (SIP) call request, the SIP call request

3   containing the telephone number in the uniform resource locator.

1   41.   (Currently Amended) The device of claim 19, wherein the generated call request

2   comprises a Session Initiation Protocol call request.

1   42.   (Cancelled)

8